



CONDUCTIVE FABRIC

BENCH HEIGHT

SERIES 10



AL10-FC



PL10-FC

Super Heavy Duty 450 lbs, Capacity, Waterfall 3" High Resilient Density Foam for Better Comfort

MODEL	Upholstery Type	Height Adjustment	Seat Dimensions	Back Dimensions	Footring	Base	Drag Chain	Caster
AL10-FC	Conductive Fabric	21"-31"	20"W x 18"D	15"W x 12"H	20"	Polished Aluminum	No	9
PL10-FC	Conductive Fabric	21"-31"	20"W x 18"D	15"W x 12"H	20"	Black Nylon	Yes	1



AM10-FC



PM10-FC

Super Heavy Duty 450 lbs, Capacity, Waterfall 3" High Resilient Density Foam for Better Comfort

MODEL	Upholstery Type	Height Adjustment	Seat Dimensions	Back Dimensions	Footring	Base	Drag Chain	Caster
AM10-FC	Conductive Fabric	21"-31"	20"W x 18"D	16"W x 16"H	20"	Polished Aluminum	No	9
PM10-FC	Conductive Fabric	21"-31"	20"W x 18"D	16"W x 16"H	20"	Black Nylon	Yes	1



AE10-FC



PE10-FC

Super Heavy Duty 450 lbs, Capacity, Waterfall 3" High Resilient Density Foam for Better Comfort

MODEL	Upholstery Type	Height Adjustment	Seat Dimensions	Back Dimensions	Footring	Base	Drag Chain	Caster
AE10-FC	Conductive Fabric	21"-31"	20"W x 18"D	19"W x 16.5"H	20"	Polished Aluminum	No	9
PE10-FC	Conductive Fabric	21"-31"	20"W x 18"D	16"W x 16"H	20"	Black Nylon	Yes	1

SERIES 20S



AM20S-FC



PM20S-FC

Super Heavy Duty 450 lbs, Capacity, Waterfall Front Contour Seat and 2.5" High Resilient Density Foam for Better Comfort

MODEL	Upholstery Type	Height Adjustment	Seat Dimensions	Back Dimensions	Footring	Base	Drag Chain	Caster
AM20S-FC	Conductive Fabric	21"-31"	18"W x 18"D	16"W x 16"H	18"	Polished Aluminum	No	9
PM20S-FC	Conductive Fabric	21"-31"	18"W x 18"D	16"W x 16"H	18"	Black Nylon	Yes	1



AL20S-FC



PL20S-FC

Super Heavy Duty 450 lbs, Capacity, Waterfall Front Contour Seat and 2.5" High Resilient Density Foam for Better Comfort

MODEL	Upholstery Type	Height Adjustment	Seat Dimensions	Back Dimensions	Footring	Base	Drag Chain	Caster
AL20S-FC	Conductive Fabric	21"-31"	18"W x 18"D	15"W x 12"H	18"	Polished Aluminum	No	9
PL20S-FC	Conductive Fabric	21"-31"	18"W x 18"D	15"W x 12"H	18"	Black Nylon	Yes	1

SERIES 20M



AM20M-FC



PM20M-FC

Super Heavy Duty 450 lbs, Capacity, Waterfall Front Contour Seat and 3" High Resilient Density Foam for Better Comfort.

MODEL	Upholstery Type	Height Adjustment	Seat Dimensions	Back Dimensions	Footring	Base	Drag Chain	Caster
AM20M-FC	Conductive	21"-31"	20"W x 18"D	16"W x 16"H	20"	Polished	No	9
PM20M-FC	Conductive Fabric	21"-31"	20"W x 18"D	16"W x 16"H	20"	Black Nylon	Yes	1



AL20M-FC



PL20M-FC

Super Heavy Duty 450 lbs, Capacity, Waterfall Front Contour Seat and 3" High Resilient Density Foam for Better Comfort.

MODEL	Upholstery Type	Height Adjustment	Seat Dimensions	Back Dimensions	Footring	Base	Drag Chain	Caster
AL20M-FC	Conductive	21"-31"	20"W x 18"D	15"W x 12"H	20"	Polished	No	9
PL20M-FC	Conductive Fabric	21"-31"	20"W x 18"D	15"W x 12"H	20"	Black Nylon	Yes	1



AE20M-FC



PE20M-FC

Super Heavy Duty 450 lbs, Capacity, Waterfall Front Contour Seat and 3" High Resilient Density Foam for Better Comfort.

MODEL	Upholstery Type	Height Adjustment	Seat Dimensions	Back Dimensions	Footring	Base	Drag Chain	Caster
AE20M-FC	Conductive Fabric	21"-31"	20"W x 18"D	19"W x 16.5"H	20"	Polished Aluminum	No	9
PE20M-FC	Conductive Fabric	21"-31"	20"W x 18"D	19"W x 16.5"H	20"	Black Nylon	Yes	1

SERIES 20W



AE20W-FC



PE20W-FC

Super Heavy Duty 450 lbs, Capacity, Waterfall 3" High Resilient Density Foam for Better Comfort

MODEL	Upholstery Type	Height Adjustment	Seat Dimensions	Back Dimensions	Footring	Base	Drag Chain	Caster
AE20W-FC	Conductive Fabric	21"-31"	21.5"W x 18"D	19"W x 16.5"H	20"	Polished Aluminum	No	9
PE20W-FC	Conductive Fabric	21"-31"	21.5"W x 18"D	19"W x 16.5"H	20"	Black Nylon	Yes	1



AL20W-FC



PL20W-FC

Super Heavy Duty 450 lbs, Capacity, Waterfall 3" High Resilient Density Foam for Better Comfort

MODEL	Upholstery Type	Height Adjustment	Seat Dimensions	Back Dimensions	Footring	Base	Drag Chain	Caster
AL20W-FC	Conductive Fabric	21"-31"	21.5"W x 18"D	19"W x 16.5"H	20"	Polished Aluminum	No	9
PL20W-FC	Conductive Fabric	21"-31"	21.5"W x 18"D	19"W x 16.5"H	20"	Black Nylon	Yes	1



AM20W-FC



PM20W-FC

Super Heavy Duty 450 lbs, Capacity, Waterfall 3" High Resilient Density Foam for Better Comfort

MODEL	Upholstery Type	Height Adjustment	Seat Dimensions	Back Dimensions	Footring	Base	Drag Chain	Caster
AM20W-FC	Conductive Fabric	21"-31"	21.5"W x 18"D	16"W x 16"H	20"	Polished Aluminum	No	9
PM20W-FC	Conductive Fabric	21"-31"	21.5"W x 18"D	16"W x 16"H	20"	Black Nylon	Yes	1

SERIES 45



A45-FC



P45-FC

Super Heavy Duty 300 lbs, Capacity, 2.5" High Resilient Density Foam for Better Comfort, Rubber Edge Banding on Seat and Back for a good Protection of Fabric and Vinyl

MODEL	Upholstery Type	Height Adjustment	Seat Dimensions	Back Dimensions	Footring	Base	Drag Chain	Caster
A45-FC	Conductive Fabric	21"-31"	18"W x 17"D	15.5"W x 13"H	20"	Polished Aluminum	No	9
P45-FC	Conductive Fabric	21"-31"	18"W x 17"D	15.5"W x 13"H	20"	Black Nylon	Yes	1

SERIES 50



50-DF

Super Heavy Duty 300 lbs, Capacity, 2.5" High Resilient Density Foam for Better Comfort

MODEL	Upholstery Type	Height Adjustment	Seat Dimensions	Back Dimensions	Footring	Base	Drag Chain	Caster
50-DF	Conductive Fabric	19"-27"	18"W x 17"D	15"W x 12"H	18"	Black Nylon	Yes	1

SERIES 60



A60-FC



P60-FC

Super Heavy Duty 300 lbs, Capacity, 2.5" High Resilient Density Foam for Better Comfort

MODEL	Upholstery Type	Height Adjustment	Seat Dimensions	Back Dimensions	Footring	Base	Drag Chain	Caster
A60-FC	Conductive Fabric	21"-31"	18"W x 17"D	15"W x 12"H	18"	Polished Aluminum	No	9
P60-FC	Conductive Fabric	21"-31"	18"W x 17"D	15"W x 12"H	18"	Black Nylon	Yes	1

Conductive Seating Features:

Industrial Seating™ conductive seating insures a safe, static-clear work area. All IST™ conductive seating models are equipped with conductive seat cushions, Back cushions, as well as all metal parts and the IST™ dual resistance system.

Isstat Group IV Fabrics ESD

• Material 98% Polyolefin, 2% Carbon Infused Nylon • Surface Resistance: 10⁶ omhs per Square

• Flamability: Pass California tech. Bulletin 117



Blue-413



Navy-421



Black-452



Grey-431



Charc.-441



L. Burg.-462

OPTIONS



DLC



ST



FLC

Controls	Description
DLC	Height and Back Tilt (This control has two levers for seat height and back angle adjustment and back height adjustment with knob)
ST	Height and Seat and Back Tilt (This control has two levers, one for height adjustment and the other for Seat and Back tilt adjustment and back height with knob)
FLC	Three Lever for Individual Lift (Height lever adjustment, seat tilt adjustment back tilt adjustment and height back adjustment with knob and a seat tension knob)



FR04



FR05



FR06

Footring	Description
FR04	Knobless Nylon Footring 18" The Footring is Loosened and Tightened by Turning the Outer Ring. (option for models 20S, 45, 50 and 60)
FR05	Knobless Aluminum with Steel Ring 20" The Footring is Loosened and Tightened by Turning the Outer Footring. (option for models 10, 20M and 20W)
FR06	Nylon Center with Steel Ring, Footring 18" (option for models 20S, 45, 50 and 60)



TF



TA



TAA

Arms	Description
TF	Fixed Height and Width, Black
TA	Fixed Height and Adjustable Width, Black
TAA	Adjustable Height and Adjustable Width



1B



1U



1UB



2

Caster	Description
1B	Braking Caster , Recommended where Chairs may roll to easily when is Not Occupied
1U	Soft Urethane Caster, Recommended on Tile, Cement and other Hard Surfaces
1UB	Soft Urethane Braking Caster, Recommended for reduce Mobility when is Not Occupied
2	Nylon Glide, Recommended for use in areas where requiring limited mobility



TF-BX-C



TA-BX-C



TAA-BX-C

Arms	Description
TF-BX-C	Fixed Height and Width, with Chrome Arm Frames & ESD Arm Pads
TA-BX-C	Fixed Height and Adjustable Width, with Chrome Arm Frames & ESD Arm Pads
TAA-BX-C	Adjustable Height and Adjustable Width, with Chrome Arm Frames & ESD Arm Pads



9B



9U



9UB



11

Caster	Description
9B	ESD Braking Caster , Recommended where Chairs may roll to easily when is Not Occupied
9U	ESD Soft Urethane Caster, Recommended on Tile, Cement and other Hard Surfaces
9UB	ESD Soft Urethane Braking Caster, Recommended for reduce Mobility when is Not Occupied
11	ESD Nylon Glide, Recommended for use in areas where requiring limited mobility